



**Item no. 322/774**  
**Manufacturer's no. V0011730**

## Battery Monitor SmartShunt, 500 A



### Information

|                |                     |
|----------------|---------------------|
| Dimensions     | 12 x 4.6 x 5.4 cm   |
| Pack size      | 13.5 x 8.5 x 7.5 cm |
| Net weight     | 300 g               |
| Gross weight   | 370 g               |
| Catalogue page | 583                 |

The SmartShunt is an all-in-one battery monitor that uses your phone as a display. The SmartShunt connects via Bluetooth to the VictronConnect app on your phone (or tablet), allowing you to conveniently read all monitored battery parameters, such as state of charge, remaining time, historical information and much more.

Alternatively, the SmartShunt can be connected and read by a GX device. The connection to the SmartShunt is made via a VE.Direct cable.

The SmartShunt is a good alternative to a BMV battery monitor, especially for systems where battery monitoring is required but less wiring and chaos are desired. The SmartShunt is equipped with Bluetooth, a VE.Direct connection and a connection that can be used for monitoring a second battery, monitoring the midpoint or connecting a temperature sensor. Input voltage: 6.5 – 70 V DC.

### Specifications

|                 |                      |
|-----------------|----------------------|
| Nominal current | 500 A                |
| Type            | SmartShunt 500A/50mV |