



Item no. 300/419
Manufacturer's no. WMMP12-116



Pressure Diaphragm Pump



Information

Dimensions	125 x 111 x 203 mm
Pack size	30.1 x 14.4 x 13 cm
Net weight	1.9 kg
Gross weight	2.19 kg
Catalogue page	439

Automatic drinking water pump with bypass control.

- High delivery rate with pulsation-free operation
- Very quiet due to four-chamber membrane technology and fully rubberised anti-vibration feet
- Flow rate up to 11.6 l/min
- With adjustable bypass control
- Adjustable pressure switch (presetting pressure switch: 2.4 bar, adjustable from 1.9 – 3.8 bar)
- Safe to run dry
- Self-priming up to a height of 4 m
- Materials suitable for drinking water
- Incl. stainless steel pre-filter strainer and hose connections
- Compatible with all UV-C LED water disinfection units of the UV-8 series and sterile filters by WM aquatec

Technical data:

- Max. delivery rate: 11.6 l/min (open flow)
- Cut-off pressure: 2.4 bar (adjustable from 1.4 – 2.8 bar)
- Water connections: 12/13 mm hose nozzle (1 x straight, 1 x angled)

Specifications

Pressure	2.4 bar
Static head	4 m
Output	11.6 l/min
Nominal capacity	38.4 W
Nominal voltage	12 V
Nominal current	3.2 A
Certified for drinking water	Yes