



Item no. 323/908

Manufacturer's no. JT-SOLO-MAN-K-2024-HA-4x4-L2-L3-L4-L5



Underfloor Box Juicetray Solo for MAN TGE from 2018

Juicetray

Information

Dimensions	97x37x72 cm
Pack size	100x72x40 cm
Net weight	30 kg
Gross weight	35 kg

With Juicetray Solo, you make optimal use of the space in your MAN TGE: the innovative underfloor battery system is securely mounted beneath the floor of the MAN TGE, creating valuable space inside – for everything that really matters to you on the road. Be it in camper conversions, service vehicles or everyday professional use: Juicetray Solo makes your MAN TGE significantly more flexible, comfortable and independent.

More space inside

Thanks to the specially tailored underfloor mounting for the MAN TGE, you gain over one cubic metre of additional storage space. This space remains entirely available for your conversion, tools, sports equipment or simply more room to move – without any restrictions to the vehicle layout.

More safety for you and your vehicle

Since the battery system is mounted outside the passenger compartment, the risk of fire inside the vehicle is significantly reduced. The housing meets protection class IP67 and is dust-tight as well as protected against temporary submersion. The Juicetray Solo underfloor box combines a robust PE casing with a KTL-coated steel base holder, specially adapted to the vehicle structure of the MAN TGE.

Flexible and future-proof

Specifications

Vehicle model	MAN TGE, van, 2017 – ...
Colour	black
Material	PE polyethylene, steel

Juicetray Solo can be combined with various battery systems and can be precisely tailored to your energy needs. Be it van life with the MAN TGE, craft use or expeditions – the system grows with your requirements and remains flexibly expandable.

The Juicetray solution is suitable for the **MAN TGE van** in the following versions:

- **Year of manufacture:** from 2018
- **Drive types:**
 - All-wheel drive (AWD)
 - Rear-wheel drive (RWD)
 - Front-wheel drive: under review
- **Vehicle lengths:** all lengths compatible

Vehicle requirements

- Recommended without spare wheel preparation.
- For vehicles with spare wheel preparation, two brackets must be removed (approx. 15 minutes effort).

Important note regarding the exhaust system

- Not compatible: exhaust systems where the exhaust pipe runs completely to the rear.
- Compatible: middle or side variants that run up to the rear axle (very rare).