



Item no. 303/132
Manufacturer's no. 60000



Push-and-Connect Quick Coupling Complete, 10 mm, ½"-IG



Information

Dimensions	35 x 133 x 18 mm
Pack size	13.3 x 4 x 1 cm
Net weight	50 g
Gross weight	50 g

The push-and-connect quick coupling enables a fast, simple and secure connection of hoses and hose systems. The integrated shut-off function ensures controlled disconnection without unwanted leakage and increases operational safety in daily use.

An elaborate shut-off mechanism with springs and coupling elements made of stainless steel, as well as multiple O-rings, guarantees precise guidance and reliable function. This ensures that the seal remains stable over the long term even at high flow rates. The quick coupling valves can be tightly connected or just as quickly disconnected with one hand.

The optimised flow behaviour combined with a large internal diameter reduces pressure losses and supports a constant flow. Installation is simple and time-saving. The quick coupling is pressure-resistant and reliably sealed up to 5 bar.

Advantages:

- Fast, secure connection of hoses and hose systems
- Integrated shut-off function for controlled disconnection
- Stainless steel components and multiple O-rings for durable sealing
- High flow rate due to optimised flow cross-section
- Simple and quick installation

Specifications

Connection	½" IG
Size	ø 10 mm
Material	POM polyoxymethylene

- Pressure-resistant and sealed up to 5 bar