



STEEL STRIPS WHEELS LTD.

Works & Regd. Office:

VILL. SOMALHERI / LEHLI,
P.O. DAPPAR, TEHSIL DERABASSI,
29 KMS. FROM CHANDIGARH - ON
CHANDIGARH-AMBALA HIGHWAY,
DISTT. PATIALA, PUNJAB (INDIA) - 140 506
Tel. : +91 (1762) 275249, 275228, 275173, 275172
Fax : +91 (1762) 275228 Email : sswlsite@sswlinia.com

05th October, 2017

Technical information for the wheel:

5.5J x 14 H2-5-30

Wheel Part No.	: SSWL160
Wheel Size	: 5.5J x 14 H2 ET30
Application	: Car Trailer
Center Hole	: $\varnothing 66.5^{+0.15}$ mm
Pitch Circle Diameter	: $\varnothing 112$ mm
No. of stud Holes	: 5
Stud Hole Size	: B12ES24
Wheel Centering	: Bolt Centering
Inset	: 30 mm
Valve Recommendation	: ETRTO- V2.01.1, V2.03.1, V2.03.2, V2.03.8
Load Capacity	: 950 Kg / LI 106 at 140 km/h
Wheel Weight	: ~ 9.9 Kg
Wheel Fastener	: Wheel Screw- M12x1.5 with Spherical Head R12
Torque Recommendation	: 120 N-m
Hub flange diameter	: Min. $\varnothing 152$ mm

We recommend circular hub to avoid negative behavior on wheel endurance.

For Steel Strips Wheels Limited


Authorised Signatory

Head Office : SCO 49-50, Sector-26, Madhya Marg, Chandigarh -160 019 (INDIA)
Tel: +91-172-2793112 / 2790979 / 2792385 Fax: +91-172-2794834 / 2790887
Website : www.sswlinia.com
Delhi Office : Room No. 398, 3rd Floor, Ashoka Hotel, 50-B, Chanakyapuri, New Delhi-110021
Tel. : 011-26878167-70, Fax : 011-26878168 Email : sswl@nde.vsnl.net.in

