



Item no. 323/585

Manufacturer's no. 669035003

Charge Controller MPPT 350 Duo

SOLARA®
module, komponenten, systeme

Information

Dimensions	147 x 40 x 74 mm
Pack size	15 x 9.5 x 5 cm
Net weight	400 g
Gross weight	800 g
Catalogue page	607

LiMoPower® MPPT DUO solar charge controller

The MPPT DUO solar charge controllers feature two charging outputs for RV and starter batteries and are compatible with lead-acid, AGM, gel and lithium batteries. The main charging output uses an IU1oU2 charging curve for optimal charging, while the second output maintains the starter battery during long periods of inactivity.

A solar monitor can optionally be connected to display different parameters. High-quality components and a microcontroller ensure maximum power yield through the MPPT method, which converts excess voltage into a higher charging current.

There is an up to 30% increase in charging current compared to conventional controllers.

- State-of-the-art MPPT technology for increased energy yield
- Standard with temperature sensor
- Optional: solar monitor for all relevant data
- Robust aluminium housing with fan
- 4 charging curves for all battery types

Specifications

Colour	black
Charging current	25.5 A
Nominal capacity	350 W
Nominal voltage	12 V
Nominal current	25.5 A
Type	MPPT 350 Duo

- Top quality at fair prices