



Item no. 451/275
Manufacturer's no. 101 08982

Hazard symbol



Warning!, H226, EUH208, EUH210, EUH212

Adhesive Set for Flexible Solar Panels



Information

Pack size	25 x 11 x 7 cm
Net weight	1 kg
Gross weight	1.1 kg

The DEKALIN Flex solar panel adhesive kit is the ideal complete package for secure and durable bonding of flexible solar panels on motorhome and caravan roofs. All included components are perfectly coordinated and allow for professional processing – completely without drilling.

The set consists of:

- DEKSAYL MS-1 (adhesion promoter) 290 ml
- DEKSAYL M-5 (high-performance adhesive based on MS polymer) 290 ml
- DEKACLEAN Ultra cloth (cleaning cloth)
- Processing instructions

Advantages:

- All-in-one set – cleaning, adhesion promotion and bonding in one step.
- Maximum safety – permanently elastic connection that reliably compensates for vibrations and movements on the vehicle roof.
- No drilling holes required – protects the roof skin and prevents the risk of leaks.
- UV- & weather-resistant – the bond withstands heat, frost, rain and sunlight.
- Easy processing – with the enclosed instructions, even beginners can manage it without problems.

Specifications

Colour white

- Clean result – quick, residue-free cleaning ensures a visually flawless bonding appearance.

This way, you have everything at hand to mount your solar panels securely and cleanly for the long term.

Application

The set was specially developed for the installation of flexible solar panels and is suitable for use on common substrates such as aluminium, GRP, painted sheet metal or plastics.

Typical areas of use:

- Roof surfaces of motorhomes and caravans
- Boat superstructures
- Trailers and expedition vehicles

Processing

1. Clean – thoroughly degrease the surface with the DEKA-CLEAN Ultra cloth.
2. Apply adhesion promoter – apply DEKSAYL MS-1 thinly to the bonding surfaces and allow to flash off briefly.
3. Bond – apply DEKSAYL M-5 in strips or beads, place the panel and press down evenly.
4. Allow to cure – depending on temperature and humidity, full strength is achieved within 24 – 48 hours.

Detailed instructions are included with the product.

Contents: 1 set

Weight: 1 kg