



**Item no. 324/103**

Manufacturer's no. 01653T60699SB

## Recessed Double Socket USB-C/USB-A



### Information

|                |              |
|----------------|--------------|
| Pack size      | 4x3.5x2.5 cm |
| Net weight     | 20 g         |
| Gross weight   | 50 g         |
| Catalogue page | 566          |

The recessed USB C/A double socket PD/QC EV without LED with integrated voltage transformer supports the fast charging method Power Delivery (port C) and Quick Charge (port A+C). With protection against reverse polarity, overload, overtemperature, overvoltage, short circuit. E1 approval.

Output 5 V, 9 V, 12 V and with 24 V input voltage also 15 V and 20 V. USB-C port up to max. 3 A (30 W), USB-A port up to max. 2.2 A (30 W). Self-consumption < 5 mA. Mounting hole  $\varnothing$  28 mm, fastening with hexagon nut, pre-assembled cable connection.

### Specifications

|                  |                            |
|------------------|----------------------------|
| Connection       | USB-A   USB-C              |
| Colour           | black                      |
| Cable length     | 15 cm                      |
| Material         | PC polycarbonate           |
| Nominal capacity | 30 W                       |
| Nominal voltage  | 12 – 24 V                  |
| Nominal current  | 2.2 A                      |
| Type             | USB-A   USB-C              |
| Variant          | without installation plate |