



Item no. 322/169

Manufacturer's no. 9620000133



Battery Control Booster MT, 60 A

BÜTTNER
→DOMETIC

Information

Dimensions	300x70x270 mm
Pack size	51.5x32.9x10.5 cm
Net weight	3.8 kg
Gross weight	4.65 kg

Due to their higher output power (30 A, 40 A, 60 A), these devices are not only suitable for parallel charging with existing charging devices, but can also be used as the main charging device. For self-conversion or van conversion, the BCBs can be mounted directly between starter and RV battery. Adjustable to wet, gel, AGM and standard LiFePO₄ battery systems.

- 1. At the 230 V mains:** the BCB provides 30 A or 40 A, which can be reduced by 10 A directly on the device.
- 2. Driving mode:** the IUoU charge is active while driving. The booster is activated with either 30 A, 40 A or 60 A depending on the current power level to ensure a full charge.
- 3. Pulser function:** as with BCB 25/20, the pulser function can be activated.

Installation: if the BCB is used as the only charging device, no high-current relay is necessary. BCB 30/30 can be installed in vehicles with integrated electronic block (EBL, CBE, etc.). This requires a „high current relay (80 A) with installation kit“.

Specifications

Cable length	5 m
Charging current	60 A
Nominal voltage	12 V
Type	MT BCB 60/40 IUoU