



Item no. 322/880
Manufacturer's no. #SPL25



Solar Panel Campere, 25 Wp



Information

Dimensions	790x190x30 mm
Pack size	80x20x4 cm
Net weight	1.45 kg
Gross weight	1.7 kg

The monocrystalline **campere** solar panels by LILIE with tested first-choice cells (78 x 39 mm) allow you to make optimum use of the available free space.

In contrast to classic series mounting, **campere** solar panels connected in parallel can also be installed with different amperages. The amperages of all panels are added together to form the total amperage. The solar panels only need to have the same voltage.

If a solar panel is partially shaded in a conventional series connection, this reduces the current yield of all other panels. The innovative parallel connection of the **campere** SPL25 and SPL105 solar panels by LILIE prevents this effect. As the voltage remains constant when connected in parallel, only the output of the partially shaded panels is reduced. All other panels continue to deliver full power.

- **Simple expansion** of the system possible thanks to plug & play, no complex cable laying necessary
- **Cost-effective expansion option**, installation work is minimal for retrofitting
- **Uncomplicated installation** with pre-configured cables and connector sets

Specifications

Short circuit current	1.33 A
No-load voltage	24 V
Number of panels	1
Nominal power solar panel(s)	25 Wp
Nominal voltage	20 V
Daily output	112 Wh
Type	SPL25

- **Combine** panels with different sizes and currents
- Individually configurable thanks to modular system
- Simple, arbitrary expansion of the solar system on the roof using accessories
- Simple connection through plug and play
- Waterproof connections
- Integrated frame
- Simply stick the panels on
- Optimum rear ventilation
- Optimum utilisation of roof area thanks to lightweight, compact panels
- Panels can be detached again if required

•
Powerful 6 mm² cable

- Panels with fitted MC4 connectors
- **Multi-zone additional yield** (Mehrzonenzusatzenertrag®) thanks to optimised cell interconnection
- Easy to expand, high performance, long service life of the panels
- Protected by patent
- Less power loss with partial shading

Certifications

- IEC 61215 Safety Class II
- IEC 61730-1, IEC 61730-2
- CE 2006/95/EC