



Item no. 323/421
Manufacturer's no. 9620013711



Hazard symbol



H225, H319, H336, H412, EUH066, EUH208, EUH210, EUH211

All-In-One Solar System Flat Light, 150 Wp

BÜTTNER
→ DOMETIC

Information

Dimensions	1380x540 mm
Pack size	154x74x17 cm
Net weight	5.9 kg
Gross weight	8.6 kg
Catalogue page	597

The ultra-flat **MT Flat Light** all-in-one solar systems include all installation accessories. Every system is equipped with high-quality components in a high-quality design. All ultra-flat solar panels are equipped with monocrystalline high-performance cells. These retain their high output voltage even in extreme external temperatures and thus guarantee high daily outputs even in southern holiday locations. The exterior cable is UV-proof, like the cable set in the interior, resistant to all environmental influences. The cable connection to the interior is routed through an extremely flat cable gland. This ensures that the installation height is extremely low. The solar control system is also state-of-the-art. Each all-in-one system is equipped with an EBL connection cable set and therefore state-of-the-art.

Scope of delivery: all-in-one solar system: ultra-flat solar panel(s) with crystalline cell technology; solar controller MPPT (MTSC330) with Bluetooth, temperature sensor and routing to the roof; cable set; cable set for vehicles with EBL; mounting material; gluing/mounting instructions.

Specifications

Short circuit current	6.36 A
No-load voltage	27.2 V
Number of panels	1
Nominal power solar panel(s)	150 Wp
Daily output	660 Wh
Type	MT 150 FL