



Item no. 350/450
Manufacturer's no. 6203805



Camping Gas Regulator Hose Line Set without Pressure Gauge

GOK

Information

Pack size	30x23x4 cm
Net weight	720 g
Gross weight	720 g
Catalogue page	524

For connection to gas cylinders, for the operation of gas appliances. **Consisting of:** low pressure regulator, medium-pressure hose 1500 mm (rubber with textile reinforcement; cold-resistant down to -30 °C; hose dimensions 6.3 x 3.5 mm), SKU-QR quick coupling, STN plug nipples and MiniTool.

- The SKU-QR quick coupling is tamper-proof due to a special device – unlocking is only possible using the standardised STN plug nipple.
- The gas flow is shut off when the hose line is disconnected.
- Thanks to the ergonomic and non-slip grip, the SKU-QR quick coupling fits well in the hand and allows easy coupling and uncoupling.
- Incl. three STN plug nipples with the following connections:
 - STN x G 1/4 LH-ÜM
 - STN x RVS 8
 - STN x 5/8 UNF-ÜM
- Individual fittings with DIN-DVGW or DVGW type test certificate or EU type examination certificate GGV

Please note: the SKU-QR quick coupling is not intended as a permanent shut-off device and must always be used in conjunction with a shut-off valve (e.g. the cylinder valve).

Specifications

Operating pressure	50 mbar
Pressure	50 mbar
Gas consumption	1,5 kg/h
Max. pressure: PS	16 bar
Variant	without pressure gauge
Packaging	retail packed